

PROTECT FOQUS™

Model FOQUS™ is a compact fog cannon for very small rooms up to 25 m2. Thanks to its lightweight design, FOQUS™ is well suited for server rooms, ATM rooms, home offices etc. FOQUS™ is often used for partial protection as it covers small areas quickly and efficiently.



Up to 5 year warranty

European quality – Danish design.
FOQUS™ comes with a 5 year warranty.



Possibility of 2 angled nozzles

FOQUS™ comes with a straight nozzle. However it can easily be exchanged with a 30° nozzle.



XTRA+ fog fluid

Sturdy, reusable fluid container with XTRA+ fog fluid: Extra white and dry fog with extended dissipation time. Quick and easy replacement without fog fluid spillage.

Features of PROTECT FOQUS™

- Discharges enough fog to cover a room up to 25 m2*
- Flexible adjustment between 8 and 25 m2 to exactly fit the size of the room*
- Fog maintenance function for up to 5 min. (previously "Pulse" function)
- Compatible with IPCard™, MultiCard™ and IntelliBox™
- Data log memory possible with IntelliSuite™
- Built-in daily, automatic battery test
- Integration with all types of alarm systems
- 100% silent in standby mode
- Prepared for 2 different angled nozzles

*It's important to perform a test firing of the installation – and not only rely on the calculation of cubic metres.

Specifications

3 time settings: 8, 16 and 25 m2*

Optional Fog Maintenance function (previously "Pulse" function)

1,1 l. reusable fluid container included

Enough fluid for 20 discharges in one container

Electronic fluid measurement

Power consumption: 700W

Mains connection: 230V, 50 Hz

Standby consumption after heating up: 55 W (on average)

Standby consumption when heat is disabled: 5-10 W

Heating time from cold: 7 min.

Re-heating time after fog discharge: 0,5-3 min.

Operating temperature (min./max.): 5/80° C.

Input: 5 signals

Output: 3 signals

On/off dipswitches for setting of fog time, signals and heating

Backup of electronics and pump (2 x 12V, 1.2 Ah)

Power backup after power failure: Up to 40 min.

Built-in automatic battery testing

Optical, audible and electrical signals/indicators

Status indicator on PCB

External status indicator

Anti-sabotage, impact-resistant steel casing

Colours available: White

Dimensions: L: 400, W: 240, H: 135 mm

Installation weight: 7 kg



PROTECT A/S · Hasselager Centervej 5 · DK-8260 Viby J

Tel.: (+45) 86 72 18 81 · Mail: info@protectglobal.com

Printing errors expected. Subject to changes to technical data.